Application No.: 10/702,239 RD-26491-6

## IN THE CLAIMS

The following claims are pending.

1-29. (canceled)

30. (original) A toroidal winding assembly comprising: a winding core; and at least one electrical conductor wound around said winding core to form a longitudinal assembly; said winding core comprising a substantially non-ferromagnetic core material; and said longitudinal assembly being bent to form a generally toroidal assembly and having a first assembly end bonded to a second assembly end.

- **31**. (withdrawn) The toroidal winding assembly of claim 30 wherein said core material comprises a core polymer.
- **32**. (withdrawn) The toroidal winding assembly of claim 31 wherein said core polymer comprises 100 parts of diglycidyl ether of bisphenol A and 10 parts of diethylene trianine.
- 33. (withdrawn) The toroidal winding assembly of claim 31 wherein said core polymer comprises a rubber.
- **34**. (original) The toroidal winding assembly of claim 30 further comprising a motion constraining material coating said longitudinal assembly.
- 35. (original) The toroidal winding assembly of claim 34 wherein said motion constraining material comprises a coating polymer.
- **36**. (original) The toroidal winding assembly of claim 35 wherein said coating polymer comprises gelatin and ammonium dichromate.

Application No.: 10/702,239 RD-26491-6

**37**. (original) The toroidal winding assembly of claim 35 wherein said coating polymer comprises polychloroprene.

- **38**. (original) The toroidal winding assembly of claim 35 wherein said coating polymer comprises styrene-butadiene-styrene co-polymer.
- 39. (original) The toroidal winding assembly of claim 30 wherein: said longitudinal assembly further comprises a winding support layer having a plurality of winding grooves, said winding support layer being disposed on said winding core; and said at least one conductor is wound in said winding grooves.
- **40**. (withdrawn) The toroidal winding assembly of claim 30 wherein said longitudinal assembly further comprises an outer shell surrounding said winding core and said at least one conductor.
- **41**. (withdrawn) The toroidal winding assembly of claim 40 wherein said outer shell comprises an outer shell material adapted to contract upon exposure to a contraction stimulus.
- 42. (withdrawn) The toroidal winding assembly of claim 40 wherein said longitudinal assembly further comprises a filler material filling an annular gap between said winding core and said outer shell.
- **43**. (withdrawn) The toroidal winding assembly of claim 40 wherein said filler material comprises a filler polymer.
- **44**. (withdrawn) The toroidal winding assembly of claim 43 wherein said filler polymer comprises solvent cast polychloroprene.

45-46. (canceled)